

Tri-Flex Loop® Expansion Loops and Seismic Connectors




I.D. (In.)	LENGTH (in.)		Pressure (PSI) @ Ambient Temperature	MOVEMENTS						Drain Port	WT. (lbs.)
	A	B		COMPRESSION (in.)	EXTENSION (in.)	PARALLEL (in.)	ROTATION "X" AXIS (°)	NON-PARALLEL "Y" AXIS (in.)			
ULTFL2SMN											
1/2	19.50	14.00	175	2	2	2	25°	1	1/4	3	
3/4	19.25	14.50	175	2	2	2	20°	1	1/4	4	
1.0	21.00	15.75	175	2	2	2	20°	1	1/2	6	
1.25	25.00	18.00	175	2	2	2	15°	1	1/2	8	
1.5	27.00	19.50	175	2	2	2	15°	1	1/2	11	
2.0	31.00	22.25	175	2	2	2	10°	1	1/2	15	
2.5	35.00	25.00	175	2	2	2	10°	1	3/4	27	
3.0	39.25	28.00	175	2	2	2	10°	1	3/4	37	
4.0	48.75	33.00	175	2	2	2	5°	1	3/4	64	

Manufactured with 5:1 safety factor. All Tri-Flex Loops are 100% hydrostatic tested at the factory to 262 psig.



Listed 536


Tri-Flex Loop® Stainless steel 1/2" - 4" for compressed and combustible gases at pressures not exceeding 175 PSI at ambient temperature. The term combustible gases, as used herein, means gases such as liquefied petroleum gases, and manufactured and natural gases.
33NB



CSA standard B-51 certified. Inspected and tested by the Technical Standards and Safety Authority of Canada.

Tri-Flex Loop® Movement Capabilities

Tri-Flex Loop is capable of handling the following movements simultaneously:



PROJECT	
CUSTOMER	
ENGINEER	
REPRESENTATIVE	
DRAWING #	



4560 Buckley Road
Liverpool, NY USA 13088-2509
315/437-1611 • Fax 315/437-1903
www.flexhose.com • 1.877.TRI FLEX

TFL2SMN-UL 1/2"-4" I.D.

Expansion & Seismic Loops UL536 Listed