


AssureFlex® Tri-Flex Loop® Expansion Loops and Seismic Connectors for Fire Protection






CSA standard B-51 certified.
Inspected and tested by the
Technical Standards and
Safety Authority of Canada.

Qty	Dimensions			Pressure (PSI) @70° F	Movement Capability					Drain Port (in.)	Wt. (lb.)	Notes
	I.D. (in.)	"A" (in.)	"B" (in.)		Compression (in.)	Extension (in.)	Parallel (in.)	Rotate "X" Axis (Deg.)	Non-parallel "Y" Axis (in.)			
	1.00	21.00	15.75	300	2.0	2.0	2.0	20°	1.0	½"	6	
	1.25	25.00	18.00	300	2.0	2.0	2.0	15°	1.0	½"	8	
	1.50	27.00	19.50	300	2.0	2.0	2.0	15°	1.0	½"	11	
	2.0	31.00	22.25	300	2.0	2.0	2.0	10°	1.0	½"	15	
	2.5	35.00	25.00	300	2.0	2.0	2.0	10°	1.0	¾"	27	
	3.0	39.25	28.00	300	2.0	2.0	2.0	10°	1.0	¾"	37	
	4.0	48.75	33.00	175	2.0	2.0	2.0	5°	1.0	¾"	64	

Working pressures shown for the hose and braid are based on an operating temperature of 70°F (21°C) with a 4:1 safety factor.

Movement Capabilities



PROJECT	
CUSTOMER	
ENGINEER	
REPRESENTATIVE	
DRAWING #	



4560 Buckley Road • Liverpool, NY USA 13088-2509
315/437-1611 • Fax 315/437-1903
www.flexhose.com • 1.877.TRI FLEX